

# BS EN 15048-1 STOCK RANGE

LENGTH (MM)	M12	M14	M16	M18	M20	M22	M24	M27	M30	M33	M36
30	X		X								
35	X		X								
40	X	X	X		X						
45	X	X	X		X						
50	X	X	X	X	X	X	X				
55	X	X	X	X	X	X	X				
60	X	X	X	X	X	X	X	X	X		
65	X	X	X	X	X	X	X	X	X		
70	X	X	X	X	X	X	X	X	X	X	X
75	X	X	X	X	X	X	X	X	X	X	X
80	X	X	X	X	X	X	X	X	X	X	X
85	X	X	X	X	X	X	X	X	X	X	X
90	X	X	X	X	X	X	X	X	X	X	X
95	X	X	X	X	X	X	X	X	X	X	X
100	X	X	X	X	X	X	X	X	X	X	X
105	X	X	X	X	X	X	X	X	X	X	X
110	X	X	X	X	X	X	X	X	X	X	X
115	X	X	X	X	X	X	X	X	X	X	X
120	X	X	X	X	X	X	X	X	X	X	X
125	X	X	X	X	X	X	X	X	X	X	X
130	X	X	X	X	X	X	X	X	X	X	X
135	X	X	X	X	X	X	X	X	X	X	X
140	X	X	X	X	X	X	X	X	X	X	X
145	X	X	X	X	X	X	X	X	X	X	X
150	X	X	X	X	X	X	X	X	X	X	X
160	X	X	X	X	X	X	X	X	X	X	X
170	X	X	X	X	X	X	X	X	X	X	X
180	X	X	X	X	X	X	X	X	X	X	X
190	X	X	X	X	X	X	X	X	X	X	X
200	X	X	X	X	X	X	X	X	X	X	X
210	X	X	X	X	X	X	X	X	X	X	X
220	X	X	X	X	X	X	X	X	X	X	X
230	X	X	X	X	X	X	X	X	X	X	X
240	X	X	X	X	X	X	X	X	X	X	X
250	X	X	X	X	X	X	X	X	X	X	X
260	X	X	X	X	X	X	X	X	X	X	X
270	X	X	X	X	X	X	X	X	X	X	X
280	X	X	X	X	X	X	X	X	X	X	X
290	X	X	X	X	X	X	X	X	X	X	X
300	X	X	X	X	X	X	X	X	X	X	X

LONGER NON-STANDARD LENGTHS AVAILABLE UPON REQUEST